

TECHNICAL DATA SHEET CONTACT PVC SHEET

DESCRIPTION

Specially formulated pressure sensitive adhesive for bonding flexible sheets of PVC between themselves and on concrete and the like. Aliphatic combination of modified PVC resins and reactivated with heat.

PROPERTIES

Colour: Colourless
Smell: Characteristic
Viscosity: 3000-6000cP
Density : 0,97g/cm³
Solid matter: 20% ±1 %

INSTRUCTIONS

Apply the product on both sides to unite (about 7 cm overlap), wait for 3 minutes (Time Open) and assemble pressure on the union by roller.
The surfaces must be dry and clean.
Open time 10 minutes at room temperature. This adhesive is reactivated by heat input. Apply in open or well-ventilated places. Uses: aprox. 250 g/m².

PRESENTATION

Tin 1000ml 12 units/box

STORAGE

Keep in fresh and dry place. Duration: 12 months.

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.